

DuPont™ FlexWrap NF

HIGH PERFORMANCE STRETCHABLE AND FLEXIBLE SELF ADHESIVE FLASHING TAPE

BUILD ENERGY EFFICIENT BUILDINGS : CREATE AIRTIGHT AND WATER TIGHT SEALS



Length: 22.9 m
Width: 22.8 cm

- ✓ Considerably helps to facilitate the creation of airtight and water tight seals around windows, door sills, chimney breasts, pipe penetrations and any custom shapes.
- ✓ Easy to install - no need for additional fasteners
- ✓ Designed to ensure continuity, compatibility and integrity with all Tyvek® breather membranes, as well as PP non-wovens and laminated membranes at penetrations

Technical Data

Thickness	1.6 mm
Coverage	5.2 m ²
Colour	black / white
Rolls per box	1
Temperature resistance	from - 30 °C till + 80 °C (temporary 100 °C)
Elongation	ca. 160 % (2.6 x of the original length)
Processing temperature	> 0 °C
UV resistance	4 months
Storage	2 years in the initial packaging, in a clean and dry environment, between 5 °C and 25 °C



DuPont™ FlexWrap NF is a stretchable and flexible tape made up of 3 components: a crimped DuPont™ Tyvek® top sheet providing a water tight layer, the butyl mass as an adhesion layer and a paper release liner. It provides excellent watertight adhesion to all Tyvek® breather membranes around non-straight penetrations, such as dormers, door sills, chimney breasts, pipe penetrations and any custom shapes.



Tyvek.

DuPont™ FlexWrap NF

INSTALLATION GUIDELINES

Installation around pipes



Installation around windows



Surface preparation

The surface must be free from dirt, moisture, ice, grease and other materials which could reduce the adhesion. DuPont™ FlexWrap NF is to be installed when dry and at temperatures above 0 °C.

Installation

- Properly position DuPont™ FlexWrap NF around the surface to seal.
- Minimize wrinkles and bubbles by smoothing the surface and by repositioning as necessary.
- Apply pressure by hand along the entire surface to achieve a good bond to the substrate. (After pressure has been applied repositioning will be difficult.)
- After completion of the installation DuPont™ FlexWrap NF has to be covered within 4 months with the appropriate building materials.
- In isolated cases there may be the necessity to fix DuPont™ FlexWrap NF with a batten and to make good seals with a cartridge sealant (for instance DuPont™ Universal Sealant).

Tel: 01275 879770

Email: tyvek.construction@dupont.com

www.tyvek.co.uk

Copyright © 7/2009 DuPont. All rights reserved. The DuPont Oval, DuPont™, The miracles of science™ and Tyvek® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates.



The miracles of science™