

Declaration of Performance

Kooltherm K12

1000.CPR.2013.K12.001

1.	Unique identification code of the product-type	Kooltherm K12
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	See product label and marking on boards
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	Thermal insulation for buildings
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Kingspan Insulation Pembroke Leominster Herefordshire HR6 9LA
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	Not relevant
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard	EN 13166:2012 Notified testing laboratory The University of Salford (NB 1145), BITS (NB 1334) and Exova (No. 1104) performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product under system 3
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	Not relevant

9. Declared performance

Essential characteristics	Performance		Harmonised technical specification
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)	d _N 30mm 1.40 d _N 40mm 1.90 d _N 50mm 2.50 d _N 60mm 3.00 d _N 70mm 3.50 d _N 80mm 4.00 d _N 90mm 4.50 d _N 100mm 5.00 d _N 120mm 6.00	EN 12667 EN 12939
	Thermal conductivity λ_D (W/(m.K))	d _N 25-44mm 0.021 d _N 45mm + 0.020	
Thickness tolerance	d _N < 50mm d _N 50-100mm d _N > 100mm	T1: ±2,0mm T1: -2,0 +3,0mm T1: -2,0 +5,0mm	EN 823
Reaction to fire		RtF E	EN 13501-1
Compressive strength		CS(10/Y)100	EN 826
Dimensional stability under specified temperature and humidity condition	48 h, 70 °C	DS(70,-)	EN 1604
	48 h, 70 °C, 90 % R.H.	DS(70,90)	
	48 h, -20 °C	DS(-20,-)	
Water permeability	Short term water absorption	NPD	EN 1609
	Closed cell content	CV	EN ISO 4590
Apparent density		AD35	EN 1602


All other essential characteristics according to EN 13166:2012 ZA.1; NPD

Where pursuant to Article 37 or 38, the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

 Peter Wilson Managing Director (name and function)	UK / 1 st July 2013 (place and date of issue)
--	---