



ETA -11/0011
Version No 2
August 2014



DECLARATION OF PERFORMANCE
TLX Gold
MFTLXGOLDCPR

1. Unique identification code of the product-type:	TLX Gold
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:	See product
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	CUAP 12.01/12 Products with radiant heat reflective component for use in thermal insulation systems of building envelopes BS EN 13859-1:2014 (BMTLXUV25CPR) Flexible sheets for waterproofing. Definitions and characteristics of underlays. Underlays for discontinuous roofing BS EN 13859-2:2014 (BMTLXUV25CPR) Flexible sheets for waterproofing. Definitions and characteristics of underlays. Underlays for walls
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Web Dynamics Ltd. Moss Lane Blackrod Bolton Lancashire BL5 5JB
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	3
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:	Not Relevant
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	The Technical Assessment Body DEUTSCHES INSTITUT FÜR BAUTECHNIK, granted a European Technical Approval - 11/0011 based on the CUAP ETA request No 12.01/12. ITT was undertaken under system 3 and test reports issued.



ETA -11/0011

Version No 2

August 2014

9. Declared Performance

Essential Characteristics		Performance	
Property	Standard	Nominal	Notified body
Mass per square meter	EN1602:1996-11	900g/m ²	Fraunhofer IBP (1004)
Declared R _{90/90} Value	EN 12667:2001	0.850m ² .K/W	BBA (0836)
Declared Emissivity ε _{90/90}	CUAP 12.01/12	0.18	Fraunhofer IBP (1004)
Resistance to Fire	EN 13501-1	Class E	MPA Stuttgart (0672)

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr Les Squires

Development Director